

Art. SALLY
HS Code 58013600
Composition Surface - EU 1007/2011
100%PL
Composition Base - EU 1007/2011
Weight m2 - DIN EN 12127
400 gr/m2 (± 5%)
Piece lenght:
30 c.a mt
Width:
>= 145 cm
Abrasion Resistance (Martindale) - UNI EN ISO 12947-1 / UNI EN ISO 12947-2
30000
Pilling Resistance - UNI EN ISO 12945-2
4
Resistance to seam slippage - UNI EN ISO 13936-2
weft 5.6mm
warp 5mm
Fastness to rubbing - UNI EN ISO 105-X12
dry 4/5
wet 4/5
Fastness to light - UNI EN ISO 105-B02
From 3/4 To 5
Dimensional stability washing - UNI EN ISO 6330
weft -0.8%
warp -1.0%
Maintenance Symbols

Slight color tone differences might be possible
Test results were gathered from various samples and therefore represent average indicative values.
CERTIFICATION ISO 9001:2015 - N. 3906625
CERTIFICATION ISO 14001:2015 - N. 3906846
CERTIFICATION ISO 45001:2018 - N. 3906846

ISO 9001
 LL-C (Certification)

ISO 14001
 LL-C (Certification)

ISO 45001
 LL-C (Certification)

Anteprima s.p.a

Via Montalese 33/35 - 59013 Montemurlo (PO) - Italy

Tel. +39 0574 875030 - Fax +39 0574 686716

P.IVA/C.F. 01804520979 PEC: anteprima@sicurezza postale.it info@antepriamessuti.it